



MODEL AC-4C-MD



MODEL AC-5C-MD



MODEL TE-5K-MD



MODEL TE-5S-MD



SERIES 4 & 5

SERIES 4 & 5	AC-4C-MD	BC-4C-MD	5C-MD	LC-5C-MD	AC-5C-MD	TE-5C-MD	TE-5K-MD	TE-5S-MD
Max Flow	14 GPM	14 GPM	14.5 GPM	14.5 GPM	17 GPM	18 GPM	18 GPM	18 GPM
Max Head	21.5 Feet	21.5 Feet	27 Feet	27 Feet	27 Feet	29 Feet	29 Feet	29 Feet
Inlet	1" FPT	1" FPT	1" FPT	1" FPT	1" FPT	1" FPT	1" FPT	1" FPT
Outlet	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT
HP	1/12	1/10	1/8	1/8	1/8	1/5	1/5	1/5
RPM	3450	3450	3450	3450	3450	3450	3450	3450
Volts	115 or 230	115 or 230	115 or 230	115 or 230	115 or 230	115 or 230	115 or 230	115 or 230
Phase	1	1	1	1	1	1	1	1
Amps	1.75 .75	1.9 0.75	1.6 0.9	1.6 0.9	2.1 1	2.1 1.05	2.1 1.05	2.1 1.05
Motor Type	Air Cooled	Blast Cooled	SUB Blue	TE/SUB Maroon	Air Cooled	TEFC	TEFC	TEFC
Elec. Connect.	Cord	Cord	Cord	Cord	Cord	Conduit Box	Conduit Box	Conduit Box
Max Int. Press.	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI	75 PSI	200 PSI
Max Liquid Temp.	190 F	190 F	130 F	130 F	190 F	190 F	200 F	250 F
Weight Packed	8.5 lbs.	8.5 lbs.	18 lbs.	18 lbs.	9.5 lbs.	15.5 lbs.	15.5 lbs.	18 lbs.
Materials in Contact	Polypropylene, Ceramic, Ceramic Magnet, Buna N *	Polypropylene, Ceramic, Viton *	Stainless Steel, Epoxy, Polypropylene, Ceramic Magnet, Buna N, Cord	Polypropylene, Ceramic, Buna N, Stainless Steel, Ceramic Magnet	Polypropylene, Ceramic, Buna N, Ceramic Magnet *	Polypropylene, Ceramic, Viton *	Carbon/Kynar, Ceramic, Viton	316 Stainless, Viton, Ceramic, Carbon Bushing

*Smooth inlet/outlet available