



MODEL TE-7R-MD



MODEL TE-7S-MD



(Self-Priming)

MODEL SP-TE-7K-MD



MODEL TE-7.5K-MD

SERIES 7 & 7.5

SERIES 7 & 7.5	TE-7R-MD	TE-7K-MD	TE-7S-MD	SP-TE-7P-MD	SP-TE-7K-MD	TE-7.5P-MD	TE-7.5K-MD
Max Flow	53 GPM	53 GPM	53 GPM	53 GPM	53 GPM	82 GPM	82 GPM
Max Head	60 FT	60 FT	57.5 FT	52 FT	52 FT	85 FT	85 FT
Inlet	1 1/2" FPT	1 1/2" FPT	1 1/2" FPT	1 1/2" FPT	1 1/2" FPT	2" MPT	2" MPT
Outlet	1" MPT	1" MPT	1" MPT	1" MPT	1" MPT	1 1/2" MPT	1 1/2" MPT
HP	3/4	3/4	1	1	1	2	2
RPM	3450	3450	3450	3450	3450	3450	3450
Volts	115/230 or 230/460	115/230 or 230/460	115/230 or 230/460	115/230 or 230/460	115/230 or 230/460	230/460	230/460
Phase	1 or 3	1 or 3	1 or 3	1 or 3	1 or 3	3	3
Amps	1 (9.7/4.9) 3 (2.2/1.1)	1 (9.7/4.9) 3 (2.2/1.1)	1 (11.8/5.9) 3 (3/1.5)	1 (11.8/5.9) 3 (3/1.5)	1 (11.8/5.9) 3 (3/1.5)	5.4, 2.7	5.4, 2.7
Motor Type	TEFC	TEFC	TEFC	TEFC	TEFC	TEFC	TEFC
Elec. Connect.	Conduit Box	Conduit Box	Conduit Box	Conduit Box	Conduit Box	Conduit Box	Conduit Box
Max Int. Press.	50 PSI	75 PSI	200 PSI	50 PSI	50PSI	60 PSI	60 PSI
Max Liquid Temp.	190 F	200 F	250 F	190 F	190 F	190 F	190 F
Weight Packed	38.5 lbs.	38.5 lbs.	49.5 lbs.	57 lbs.	57 lbs.	53 lbs.	53 lbs.
Suction Lift	0	0	0	12 Feet	12 Feet	0	0
Materials in Contact	Polypropylene, Ryton, Ceramic, Ryton/Teflon/Carbon/Bushing, Viton *Available with 1HP motor	Carbon Filled Kynar, Carbon Bushing, Viton *Available with 1HP motor	316 Stainless Steel, Ceramic, Carbon Bushing, Viton	Polypropylene, Ceramic, Carbon Bushing, Viton	Carbon Filled Kynar, Ceramic, Carbon Bushing, Viton	Polypropylene, Ceramic, Carbon Bushing, Viton	Natural Kynar, Ceramic, Carbon Bushing, Viton

