



EBARA

Ahead  *Beyond*

Model 3U

End Suction Centrifugal Pump



PUMP SUPPLY
INCORPORATED



Model 3U

Features

- Close coupled design – saves space; simplifies maintenance and installation
- Stainless steel end components – high quality; corrosion resistance
- Versatile mounting – can be installed horizontally or vertically
- Back pullout construction – allows for assembly and overhaul of the impeller and seal without distorting suction and discharge connections
- Top centerline discharge and foot support under casing – ensures self-venting and reduces misalignment from pipe loads
- High efficiency – lowers operating costs
- High quality mechanical shaft seals and o-rings – available for standard pumping requirements, or optional high temperature and chemical duty operation
- Available as a complete pump or as a kit

Specifications


- Suction Size: 2” to 3”
- Discharge Size: 1 1/4” - 2 1/2”
- Power Range: 1 to 30 hp
- Capacity: 5 to 633 gpm
- Head: 9 to 282 feet
- Liquid: Clean Water, Glycol, Dielectric Fluid

Applications

- Pressure Boosting
- Plant Services
- Irrigation
- Water Supply Systems
- Liquid Transfer
- Ultrapure Water Systems
- Water Reclamation and Treatment
- Temperature Control
- Air Conditioning Systems

Performance Range


Nominal Speed 3450 RPM



- | | | |
|-------------------|------------------|-------------------|
| 1. 3U65-125-7.5HP | 5. 3U65-160-10HP | 9. 3U65-200-20HP |
| 2. 3U65-125-10HP | 6. 3U65-160-15HP | 10. 3U65-200-25HP |
| 3. 3U65-125-15HP | 7. 3U65-160-20HP | 11. 3U65-200-30HP |
| 4. 3U65-125-20HP | 8. 3U65-160-25HP | |

*Three phase motor only

Nominal Speed 1725 RPM



Certified to NSF/ANSI/CAN 61 & 372

*Note: Model 3U with seal code "C" is certified

