

mody ELECTRIC SUBMERSIBLE DRAINAGE PUMP

G-1006 SERIES

PORTABLE ELECTRIC SUBMERSIBLE PUMP FOR CORROSIVE & ABRASIVE APPLICATIONS

.....

Model G-1006T

6" (150mm) NPT or Hose

58 HP (43kW) @ 60 Hz

(Low Volume - High Head)

.....

G-1006 DESIGN ADVANTAGES


- Stainless Steel Strainer, Shaft, Impeller, Outlet and Hardware for maximum corrosion resistance.
- Choice of impeller materials:
 - 1) 304/316 Stainless Steel for sea water and corrosive applications and;
 - 2) Nitride Hardened 410 Stainless Steel for abrasive applications. (Standard)
- Tandem Tungsten Carbide/Tungsten Carbide and Tungsten Carbide/Tungsten Carbide mechanical seals.
- Mechanical Seals in wholly enclosed cast iron oil chamber.
- Field adjustable Nitrile Rubber-lined Diffuser/Wear Plate Optimizes efficiency throughout the life of the pump.
- Automatic ON/OFF/ON Thermal Overloads embedded in Stator Winding Optional - requires 6 core or Control cable and external controls.
- Available in complete 316 Stainless Steel Construction with Silicon Carbide/Silicon Carbide Mechanical Seals and Viton® Elastomers.



Illinois Location:
 (847) 841-7867
 860 Church Rd Elgin, IL 60120


Minnesota Location:
 (651) 758-7867
 330 Mill Bay South Suite :
 Afton, MN 55001

PumpSupplyInc.com



mody ELECTRIC SUBMERSIBLE DRAINAGE PUMP

G-1006 SERIES 58HP @ 60Hz



G-1006 SERIES

MATERIALS OF CONSTRUCTION AND ENGINEERING DATA

MOTOR

2-pole induction **continuous rated** motor with squirrel cage rotor.
 Stator insulation class 'H' (180°C)
 Speed : 3400 RPM @ 60 Hz, 2800 RPM @ 50 Hz
 Power Rating : 58HP @ 60 Hz Full Load
 Current FLA: 64 Amps @ 460v.
 Max. temperature of the pump liquid : 104°F/40°C
 Max. start/stop per hour : 15
 Star - Delta Starting Optional

POWER SUPPLY

3 phase, 50/60 Hz, AC Supply. Available in any voltage frequency combination. (380/415/460/575/1000V)

BALL BEARINGS

Single row deep groove upper bearing. Double angular contact lower bearings. The bearings are enclosed with high temperature grease-containing special Anti-corrosion additive.

POWER CABLE

Waterproof/oil proof, rubber-insulated, neoprene-sheathed copper conductor flexible cable, 50ft. (15m) length standard. Type SOOW in North America, EPR in the Middle East and HO7RN in the EU. 6 Core or Control cable with thermal overloads optional.

SHAFT SEAL

Tandem Tungsten Carbide/Tungsten Carbide and Tungsten Carbide/Tungsten Carbide Mechanical seals wholly enclosed in an oil chamber.

CORROSION RESISTANT

Epoxy coated Steel Outer Casing
 Cast Iron Stator Casing
 Nitrile Rubber- Lined Diffuser/Wear plate.
 Shaft: 431 Stainless Steel
 Hardware: 304 Stainless Steel
 Impeller: Nitride Hardened 410SS to 56HRC is Standard.
 pH range 6 - 11

STRAINER

304 Stainless Steel with 0.5" (13mm) round holes.

SUBMERGENCE


Submergence below liquid surface min 5" (127mm) max. 50' (15m).

WEIGHTS (Approx. without cable)

G 1006: 825lbs. (375Kg)

PERFORMANCE CURVE

PUMP MODEL : G 1006 T



Due to continuous product development, specifications are subject to change without notice.

03.10.Rev.0