



HullVac Series

Single & Two-Stage Rotary Piston Vacuum Pumps

Performance Specs	
Single-stage vacuum pumps	
Nominal Capacity	52 - 850 CFM
Motor Size	3 - 40 HP
Two-stage vacuum pumps	
Nominal Capacity	32 - 340 CFM
Motor Size	3 - 20 HP

Offered as a single or two-stage model, the Dekker HullVac Rotary Piston Vacuum Pumps are expertly engineered for reliability and longer lifecycles. With great performance, low maintenance, and ease of use, these pumps are built for the toughest industrial environment. The HullVac line is affordable and can save money on energy costs with their efficient design.

Features

- Sealed Bearings - Bearing life is enhanced by isolating them from harmful process grit and solvents
- Heavy duty studs, springs and wear plates are mounted to hardened steel seats designed to prevent broken springs from falling into the pumping chamber
- Internal Sealing Fluid Channels - Sealing oil enters the pumping chambers through internal channels
- Oil Flow Indicator - An oil stream splashes onto the site port ensuring easy verification even when oil is opaque
- Redundant Shaft Seals
- One piece construction of caged hinge bar enhances wear life and reduces operating noise

Illinois Location:
(847) 841-7867
860 Church Rd Elgin, IL 60123

Minnesota Location:
(651) 758-7867
330 Mill Bay South Suite 1511
Afton, MN 55001

PumpSupplyInc.com

