


**MODEL LC-3CP-MD**



**MODEL AC-3CP-MD**



**MODEL BC-3CP-MD**



**SERIES 3**

**SERIES 3**

SERIES 3	LC-3CP-MD	AC-3CP-MD	BC-3CP-MD	BC-3K-MD
<b>Max Flow</b>	8.5 GPM	10 GPM	10 GPM	10 GPM
<b>Max Head</b>	19 Feet	20.5 Feet	20.5 Feet	20.5 Feet
<b>Inlet</b>	3/4" FPT	3/4" FPT	3/4" FPT	3/4" FPT
<b>Outlet</b>	1/2" MPT	1/2" MPT	1/2" MPT	1/2" MPT
<b>HP</b>	1/20	1/15	1/15	1/15
<b>RPM</b>	3450	3450	3450	3450
<b>Volts</b>	115 or 230	115 or 230	115 or 230	115 or 230
<b>Phase</b>	1	1	1	1
<b>Amps</b>	2.0 1.0	2.3 0.9	2.1 0.9	2.1 0.9
<b>Motor Type</b>	TE/SUB Maroon	Air Cooled	Blast Cooled	Blast Cooled
<b>Elec. Connect.</b>	Cord	Leads	Leads	Leads
<b>Max Int. Press.</b>	25 PSI	50 PSI	50 PSI	75 PSI
<b>Max Liquid Temp.</b>	130 F	190 F	190 F	200 F
<b>Weight Packed</b>	8.5 lbs.	7 lbs.	8 lbs.	8 lbs.
<b>Materials in Contact</b>	Polypropylene, Epoxy, Cupric Nickel, Buna N, Ceramic Magnet	Polypropylene, Ceramic Magent, Ceramic, Buna N *	Polypropylene, Ceramic, Ceramic, Viton *	Kynar, Ceramic, Viton *

\*Smooth inlet/outlet available

