


mody ELECTRIC SUBMERSIBLE DRAINAGE PUMP

M-150/200/300/400 SERIES 2HP(1.5kW) / 3HP(2.2kW) / 4HP(3kW) / 5HP(3.7 kW)

MODEL A

M-154T	25 1/4"
M-154S/T	26 1/4"
M-204T	26 1/4"
M-204S/T	28 1/2"
M-304T	28 1/2"
M-404T	27 1/2"



M-150/200/300/400 SERIES

MATERIALS OF CONSTRUCTION AND ENGINEERING DATA

MOTOR

2-pole induction **continuous rated** motor with squirrel cage rotor.
 Stator insulation class 'H' (180°C)
 Speed : 3400 RPM @ 60 Hz, 2800 RPM @ 50 Hz
 Power Rating : 2/3/5HP @ 60 Hz, 1.5/2.2/3kW @ 50Hz Full Load
 Current FLA: 3.8, 4.9, 7.1 Amps @ 460v. 4.4, 5.5, 8 Amps @ 400v.
 Max. temperature of the pump liquid : 104°F/40°C
 Max. start/stop per hour : 15

POWER SUPPLY

3 phase, 50/60 Hz, AC Supply. Available in any voltage frequency combination. (208/220/230/380/415/460/575/1000V)

BALL BEARINGS

The rotor shaft is carried in two single row, deep groove ball bearings. The bearings are enclosed with high temperature grease-containing special Anti-corrosion additive.

POWER CABLE

Waterproof/oil proof, rubber-insulated, neoprene-sheathed copper conductor flexible cable, 50ft. (15m) length standard. Type SOOW in North America, EPR in the Middle East and HO7RN in the EU. 6 Core with thermal overloads optional.

SHAFT SEAL

Tandem Tungsten Carbide/Tungsten Carbide and Tungsten Carbide/Tungsten Carbide Mechanical seals wholly enclosed in a pressure compensated oil chamber.

CORROSION RESISTANT

Epoxy coated Extruded Aluminum Outer Casing
 Epoxy coated Extruded Aluminum Stator Casing
 Nitrile Rubber- Lined Diffuser/Wear plate. Polyurethane Optional.
 Shaft: 431 Stainless Steel
 Hardware: 304 Stainless Steel
 Impeller: Nitride Hardened 410SS to 56HRC is Standard.
 pH range 5 - 8

STRAINER

304 Stainless Steel with 1/4" (6mm) Round Holes

SUBMERGENCE

Submergence below liquid surface min 5" (127mm) max. 50' (15m).

WEIGHTS (Approx. without cable)

M 154:	62 lbs. (28Kg)
M 154S:	77 lbs. (35Kg)
M 204:	77 lbs. (35Kg)
M 204S:	88 lbs. (40Kg)
M 304:	88 lbs. (40Kg)
M 404:	79 lbs. (36Kg)



PERFORMANCE CURVES

MODEL: M154T/204T/304T/404T (50/60 Hz)

